

AD A 154459

MEMORANDUM REPORT BRL-MR-3437



THE INITIATION AND GROWTH OF ADIABATIC SHEAR BANDS

Thomas W. Wright Romesh C. Batra

April 1985

APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED.

US ARMY BALLISTIC RESEARCH LABORATORY ABERDEEN PROVING GROUND, MARYLAND

Destroy this report when it is no longer needed. Do not return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U. S. Department of Commerce, Springfield, Virginia 22161.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
MEMORANDUM REPORT BRL-MR-3437	·	
1. TITLE (and Subtitle)		S. TYPE OF REPORT & PERIOD COVERED
The Initiation and Growth of Ad	iabatic	
Shear Bands		6. PERFORMING ORG. REPORT NUMBER
		o. PERIORMINO CIG. NE. CIT. NOMBER
7. AUTHOR(s)		8. CONTRACT OR GRANT NUMBER(s)
Thomas W. Wright and Romesh C.	Ratra*	
Thomas we wright the Romosh C.	bacia	
9. PERFORMING ORGANIZATION NAME AND ADDRE	ESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
US Army Ballistic Research Labo	ratory	AREA & WORK UNIT NUMBERS
ATTN: AMX BR - TBD		
Aberdeen Proving Ground, MD 21	.005-5066	
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE
US Army Ballistic Research Labo	oratory	April 1985
ATTN: AMXBR-OD-ST Aberdeen Proving Ground, MD 21	005-5066	26
14. MONITORING AGENCY NAME & ADDRESS(If diffe	erent from Controlling Office)	1S. SECURITY CLASS. (of this report)
		Unclassified
		15e. DECLASSIFICATION/DOWNGRADING
		SCHEDULE
Approved for public release; di	stribution is unli	mited.
Approved for public release; di		
17. DISTRIBUTION STATEMENT (of the ebatrect ente		
17. DISTRIBUTION STATEMENT (of the obstract ente		
17. DISTRIBUTION STATEMENT (of the ebatrect ente		
17. DISTRIBUTION STATEMENT (of the ebstrect ente		
17. DISTRIBUTION STATEMENT (of the obstract ento 18. SUPPLEMENTARY NOTES *U of Missouri - Rolla	red in Block 20, if different fro	m Report)
17. DISTRIBUTION STATEMENT (of the ebstrect enter 18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side if necessar	red in Block 20, if different fro	m Report)
17. DISTRIBUTION STATEMENT (of the obstroct ento 18. SUPPLEMENTARY NOTES *U of Missouri - Rolla	red in Block 20, if different fro	m Report)
17. DISTRIBUTION STATEMENT (of the obstract ento 18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side if necessar Finite Element Analysis Stress Strain Relations	red in Block 20, if different fro y and identify by block number, Viscoelast	m Report) icity sses
17. DISTRIBUTION STATEMENT (of the obstrect enter 18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side if necessar Finite Element Analysis	y and identity by block number, Viscoelast Shear Stre	n Report) icity sses Conditions
18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side if necessar Finite Element Analysis Stress Strain Relations Thermal Properties Plastic Properties	y and Identity by block number, Viscoelast Shear Stre Adiabatic (Plastic De	n Report) icity sses Conditions
18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side if necessar Finite Element Analysis Stress Strain Relations Thermal Properties Plastic Properties	y and identify by block number, Viscoelast Shear Stre Adiabatic (Plastic De	icity sses Conditions formation
17. DISTRIBUTION STATEMENT (of the obstract entering in the content of the obstract entering in the supplementary notes *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side if necessary finite Element Analysis Stress Strain Relations Thermal Properties Plastic Properties 20. ABSTRACT (Continue on reverse side if necessary A simple version of thermo/visc	y and identify by block number, Viscoelast Shear Stre Adiabatic (Plastic De	icity sses Conditions formation v is used to model the forma-
17. DISTRIBUTION STATEMENT (of the obstract enter 18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side if necessar Finite Element Analysis Stress Strain Relations Thermal Properties Plastic Properties 20. ABSTRACT (Continue on reverse side if necessary A simple version of thermo/visotion of adiabatic shear bands in	y and identity by block number, Viscoelast Shear Stre Adiabatic (Plastic De: r and identity by block number) coplasticity theory in high rate deform	icity sses Conditions formation r is used to model the forma- mation of solids. The one
17. DISTRIBUTION STATEMENT (of the obstract enter 18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side if necessar Finite Element Analysis Stress Strain Relations Thermal Properties Plastic Properties 20. ABSTRACT (Continue on reverse side if necessary A simple version of thermo/visotion of adiabatic shear bands if dimensional shearing deformations.	y and identity by block number, Viscoelast Shear Stre Adiabatic (Plastic De: Tend identity by block number) coplasticity theory in high rate deform	icity sses Conditions formation is used to model the forma- mation of solids. The one is considered. For the con
18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side it necessar Finite Element Analysis Stress Strain Relations Thermal Properties Plastic Properties 20. ABSTRACT (Continue on reverse side it necessar A simple version of thermo/visotion of adiabatic shear bands it dimensional shearing deformatic stitutive assumptions made in the street of the second stitutive assumptions made in the second street of the second stitutive assumptions made in the second street of the second stitutive assumptions made in the second street of the second	y and identity by block number, Viscoelast Shear Stree Adiabatic (Plastic Description of a finite slab this paper, homogen	icity sses Conditions formation r is used to model the forma- mation of solids. The one o is considered. For the con-
18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side it necessar Finite Element Analysis Stress Strain Relations Thermal Properties Plastic Properties 20. ABSTRACT (Continue on reverse side it necessar A simple version of thermo/visc tion of adiabatic shear bands in dimensional shearing deformatic stitutive assumptions made in the stress/strain response curve the	y and Identity by block number, Viscoelast Shear Stre Adiabatic (Plastic De: Toplasticity theory in high rate deform on of a finite slab this paper, homogen nat always has a ma	icity sses Conditions formation is used to model the forma- nation of solids. The one is considered. For the cor neous shearing produces a eximum when strain and rate
18. SUPPLEMENTARY NOTES *U of Missouri - Rolla 19. KEY WORDS (Continue on reverse side if necessar Finite Element Analysis Stress Strain Relations Thermal Properties Plastic Properties 20. ABSTRACT (Continue on reverse side if necessar A simple version of thermo/visc tion of adiabatic shear bands in dimensional shearing deformatic stitutive assumptions made in the street of	v and Identity by block number, Viscoelast Shear Stre Adiabatic (Plastic De: v and Identity by block number) coplasticity theory in high rate deform on of a finite slab this paper, homoger nat always has a mail thermal softening	icity sses Conditions formation is used to model the formation of solids. The one of is considered. For the confecus shearing produces a eximum when strain and rate of are taken into account.

DD 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered) conditions. The resulting initial/boundary value problem is solved by the finite element method for one set of material parameters. The shear band grows slowly at first, then accelerates sharply, until finally the plastic strain rate in the center reaches a maximum, followed by a slow decline. Stress drops rapidly throughout the slab, and the central temperature increases rapidly as the peak in strain rate develops.

TABLE OF CONTENTS

	Page
	LIST OF FIGURES
I.	INTRODUCTION AND FORMULATION OF THE PROBLEM
II.	CONSTITUTIVE FUNCTIONS
III.	NONDIMENSIONAL VARIABLES AND HOMOGENEOUS SOLUTIONS 10
IV.	RESPONSE TO PERTURBATIONS
	REFERENCES
	DISTRIBUTION LIST

LIST OF FIGURES

Figur	<u>e</u>	Page
1.	Shearing of a finite block of material with displacement u and temperature change θ	. 15
2.	Yield surface in stress-temperature space	15
3.	Stress-strain response curves for a block of material in shear .	. 16
4.	Temperature distribution in a finite block of material at various times as a shear band forms	16
5.	Stress, temperature, and plastic strain rate vs. time near the center of a block of material as a shear band forms	17
6.	Stress, temperature, and plastic strain rate vs. time near the edge of a block of material as a shear band forms	17

I. INTRODUCTION AND FORMULATION OF THE PROBLEM

Adiabatic shear is the name given to a localization phenomena that is important in many problems involving high rate deformation of solids. In the last five years or so there has been strong interest in the theoretical aspects of the subject. Clifton, et al. have listed and briefly described more than a dozen papers on rapid shearing deformation in the recent literature, as well as several of the earlier pioneering works. However, there still appears to be a need to define a theoretically complete framework for the phenomenon and to find and examine dynamic solutions within such a framework. This paper summarizes our work to date in attempting to fill that need.

A general theory of thermoplasticity, due to Green and Naghdi, has been taken as the starting point. In their theory, which is rate independent, plastic strain and work hardening are modeled as internal variables controlled by evolutionary equations. In this paper those general features are retained, but in addition the yield function is taken to depend on plastic strain rates, as well as stress and temperature, in a manner similar to that used by Rubin and Drysdale. This combination is completely self consistent in a thermodynamic sense and allows for smooth and continuous transitions between elastic and viscoplastic states. Details will be given elsewhere, Wright and Batra. and only a summary of the equations are given here.

Figure 1 shows a block of material lying between Y = -H and Y = +H and undergoing only horizontal motion in the X direction. This motion is volume preserving and may be written as

$$x = X + u(Y,t),$$

$$y = Y,$$

$$z = Z.$$
(1)

¹R. J. Clifton, J. Duffy, K. A. Hartley, and T. G. Shawki, "On Critical Conditions for Shear Band Formation at High Strain Rates," <u>Scripta Metallurgica</u> 18, p. 443-448 (1984).

²A. E. Green and P. M. Naghdi, "A General Theory of an Elastic-Plastic Continuum," Arch. Rat. Mech. Anal. 18, p. 252-281 (1965).

³M. B. Rubin, "A Thermoelastic-Viscoplastic Model with a Rate-Dependent Yield Strength," J. Appl. Mech. 49, p. 305-311 (1982).

⁴W. H. Drysdale, "The Theory of Plasticity with Rate Effects," ARBRL-TR-02559, ADA 142 102, May 1984, Ballistic Research Laboratory, Aberdeen Proving Ground, MD.

⁵T. W. Wright and R. C. Batra, "Adiabatic Shear in Simple and Dipolar Materials," to appear (1985).

The balance relations for momentum, energy, and entropy in the absence of body forces and external sources of heat may be written

$$s_{,\gamma} = \rho \ddot{u},$$

$$\rho \dot{U} = s\dot{u}_{,\gamma} - q_{,\gamma},$$
(2)

$$\rho \ T \ \dot{\eta} \ - \frac{q}{T} \ T_{,Y} \ + \ q_{,Y} \ge 0.$$

In these equations s is the shear stress on the planes of constant Y, U is internal energy, q is heat flux due to conduction, T is temperature, η is specific entropy, and ρ is density, which is constant. The dot and the comma indicate differentiation with respect to time t and the material coordinate Y respectively, and it is assumed in the usual way that shear strain may be decomposed into elastic and plastic parts

$$\gamma = u_{,\gamma} = \gamma_e + \gamma_p . \tag{3}$$

With κ taken to be a measure of work hardening, it is assumed that a yield or loading function f exists such that

$$f(s,T,\dot{\gamma}_p) = \kappa , \qquad (4)$$

where f is monotonically decreasing in $\dot{\gamma}_p$, and the criterion for elastic or plastic loading is simply

$$f(s,T,0) \le \kappa$$
, elastic,
 $f(s,T,0) > \kappa$, plastic. (5)

If plastic deformation is occurring, the sign of $\dot{\gamma}_p$ is taken to be the same as that of s, and its absolute value may be found uniquely from (4) because of the assumed monotonicity of f. If plastic deformation is not occurring, then of course $\dot{\gamma}_p = 0$. The situation is shown schematically in Figure 2. When the stress and temperature lie in the cross hatched region, deformation is wholly elastic, but when they lie outside, the plastic strain rate is nonzero. Furthermore, the farther outside that the point (s,T) lies, the larger the absolute value of $\dot{\gamma}_p$. Equation (4) is similar to the yield functions used by Rubin³ and Drysdale.⁴ but the treatment that follows here is somewhat different from either of theirs. The work hardening parameter is assumed to obey the following evolutionary equation,

$$\dot{\kappa} = M \dot{\gamma}_{p} . \tag{6}$$

M is a constitutive function that depends only on s. T and K.

II. CONSTITUTIVE FUNCTIONS

For computational purposes specific constitutive functions have been chosen as follows.

$$\rho U = \frac{1}{2} \mu \gamma_{e}^{2} + \rho T_{0} c_{v} (e^{(\eta - \eta_{0})/c} v - 1) ,$$

$$q = -k T_{y} ,$$
(7)

where μ is a constant shear modulus, \textbf{T}_0 is a reference temperature, \textbf{c}_v is the specific heat at constant volume, and k is the thermal conductivity. Standard thermodynamic arguments show that

$$s = \mu \gamma_e$$
 , $T = T_0^e (\eta - \eta_0)/c_v$, (8)

so that the elastic response is linear, and there is no thermoelastic effect.

It is further assumed for a slow isothermal reference test at temperature T_0 that $s=\kappa=\hat{\kappa}(\epsilon)$, where ϵ is the plastic strain in that case, and that whatever the rate of deformation, κ depends only on the plastic work done. Thus it follows that

$$\dot{W}_{p} = \kappa \dot{\varepsilon} = s\dot{\gamma}_{p} ,$$

$$M = \frac{1}{\kappa} \frac{d\hat{\kappa}}{d\varepsilon} s ,$$

$$(9)$$

where $\frac{d\hat{\kappa}}{d\epsilon}$ may be expressed as a function of κ . To complete the constitutive assumptions, the yield function and $\hat{\kappa}(\epsilon)$ were chosen as follows.

^{*}This scheme may be readily generalized to multidimensional states or to the case of dipolar stresses, Wright and Batra. 5 since it turns out that all plastic rates may be related by a single proportional factor, as in Green and Naghdi 2 and Green, McInnis, and Naghdi .6 Then it is the proportional factor that is determined from the analog of (4) rather than $\dot{\gamma}_p$ itself.

⁶A. E. Green, B. C. McInnis, and P. M. Naghdi, "Elastic-Plastic Continua with Simple Force Dipole," Int. J. Eng. Sci. 6, p. 373-394 (1968).

$$|s| = \kappa (1 - a\theta) (1 + b \dot{\gamma}_p)^m ,$$

$$\hat{\kappa}(\varepsilon) = \kappa_0 (1 + \frac{\varepsilon}{\varepsilon_0})^n ,$$
(10)

where θ = T - T₀. It will be recognized that the viscoplastic effect in the present case comes from a multiplicative overstress factor, although (4) is sufficiently general to include an additive overstress or many other possibilities.

III. NONDIMENSIONAL VARIABLES AND HOMOGENEOUS SOLUTIONS

With nondimensional variables defined by

$$Y = H\overline{Y}, u = H\overline{u}, s = \kappa_{0}\overline{s}, \theta = \frac{\kappa_{0}}{\rho c_{V}}\overline{\theta}$$

$$t = \frac{1}{\dot{\gamma}_{0}}\overline{t}, \gamma = \overline{\gamma}, \kappa = \kappa_{0}\overline{\kappa}, \epsilon = \overline{\epsilon},$$
(11)

where $\dot{\gamma}_0$ is the average strain rate imposed in the problem, the complete equations in nondimensional form become

Momentum:
$$s_{Y} = \frac{\rho H^2 \dot{\gamma}_0^2}{\kappa_0} \ddot{u}$$
,

Energy:
$$\dot{\theta} = \frac{k}{\rho c_{v} \dot{\gamma}_{0} H^{2}} \theta,_{YY} + \kappa \dot{\epsilon}$$
,

Constitutive:
$$\dot{s} = \frac{\mu}{\kappa_0} (\dot{\gamma} - \dot{\gamma}_p)$$
,
$$\kappa = (1 + \frac{\varepsilon}{\varepsilon_0})^n$$
, (12)

$$\kappa \dot{\varepsilon} = s \dot{\gamma}_p (= \dot{W}_p)$$
,

Yield Surface:
$$|s| = (1 - \frac{a\kappa_0}{\rho c_y} \theta) (1 + b\dot{\gamma}_0\dot{\gamma}_p)^m \kappa$$

where the overbars have been dropped, and $(12)_6$ is subject to (5). There are two relative length scales implicit in (12), namely a thermal length

$$\sqrt{\frac{k}{\rho c}_v \dot{\gamma}_0^{H^2}}$$
 , and a viscous length $\frac{b}{H} \, \sqrt{\frac{\kappa_0}{\rho}}$. In addition there are seven

other nondimensional parameters in (12) which are required to define the mass, elastic modulus, thermal softening, work hardening, and rate hardening of the material.

In a homogeneous deformation the true displacement field has the form $u=\dot{\gamma}_0 Yt$, where $\dot{\gamma}_0$ is a constant strain rate, or with nondimensional variables u=Yt, and nondimensional values of s, θ , γ_p , κ , and ϵ depend only on time. For this case the equations become ordinary differential equations with initial values

$$s(0) = 1, \ \theta(0) = 0, \ \varepsilon(0) = 0,$$
 (13)

where time is counted from the first onset of plastic flow, and $\dot{\gamma}_p$ is to be found from (12)₆. Equation (12)₁ is satisfied identically, and (12)₂ with (12)₄ substituted for κ can be integrated immediately to give $\theta(\epsilon)$. The remaining two equations may now be written as the autonomous pair

$$\dot{s} = \frac{\mu}{\kappa_0} (1 - \dot{\gamma}_p) , s(0) = 1 ,$$
(14)

$$\dot{\varepsilon} = \frac{s\dot{\gamma}_p}{\left(1 + \frac{\varepsilon}{\varepsilon_0}\right)^n} , \quad \varepsilon(0) = 0 ,$$

where

$$\theta(\varepsilon) = \frac{\varepsilon_0}{1+n} \left(1 + \frac{\varepsilon}{\varepsilon_0}\right)^{1+n} - 1 ,$$

$$\dot{\gamma}_p = \frac{1}{b\dot{\gamma}_0} \left[\left(\frac{s}{\left(1 + \frac{\varepsilon}{\varepsilon_0}\right)^n \left(1 - \frac{a\kappa_0}{\rho c_v} \theta(\varepsilon)\right)} \right)^{\frac{1}{m}} - 1 \right] .$$
(15)

Although solutions to (14) cannot be given explicitly, some of their features can be described qualitatively. 5 In particular, for the constitutive and yield functions chosen here, s always has a simple maximum at a critical value of γ , the exact value of which is influenced by work hardening, heat capacity, rate sensitivity, thermal softening, and yield strength, the

first three tending to retard the peak, the last two to advance it. Figure 3 shows the homogeneous stress strain response for one particular choice of nondimensional parameters, as follows:

$$\frac{\rho \dot{\gamma}_0^2 H^2}{\kappa_0} = 3.928 \times 10^{-5} , \frac{k}{\rho c_v H^2 \dot{\gamma}_0} = 3.978 \times 10^{-3} , \frac{a \kappa_0}{\rho c_v} = 0.4973 ,$$

$$\frac{\mu}{\kappa_0}$$
 = 240.3 , n = 0.09 , ϵ_0 = 0.017 , $\dot{\gamma}_0 b$ = 5 x 10^5 , m = 0.02.

IV. RESPONSE TO PERTURBATIONS

Other analyses (e.g., Burns⁷ or Shawki, et al.⁸) have indicated that if a small perturbation is added to the homogeneous response, its amplitude will begin to grow once the peak stress for homogeneous deformation has been passed. The perturbation could be applied to any of the field variables, but in this paper a small symmetric temperature bump was added at the center of the slab just before the peak stress, and the problem was restarted as an initial/boundary value problem, the material parameter remaining exactly as before. The boundary values are

$$v(\pm 1,t) = \pm 1, \quad \theta_{,v}(\pm 1,t) = 0$$
, (16)

so that the average strain rate in the strip [-1,+1] is maintained, and the strip is adiabatic overall. The problem was solved by the finite element method; for details, see Wright and Batra. Some of the principal results are shown in Figures 4, 5, and 6.

Figure 4 shows a cross section of the temperature at various times after introduction of the perturbation. On this scale the peak in the initial temperature itself does not show since it is only 0.02 higher than the surrounding ambient value, which is reached at $Y = \pm 0.1$ on either side of the central peak. Only half of the central part is shown since the profile is symmetric and remains flat on out to ± 1 . Cross sections of plastic strain rate also show a strong central peak at late times.

Figure 5 shows the stress, plastic strain rate, and temperature as functions of time at a point very near to the center of the band. The plastic rate begins a slow increase, which is actually exponential at

⁷T. J. Burns, "Approximate Linear Stability Analysis of a Model of Adiabatic Shear B**a**nd Formation," Sandia Report SAND83-1907, October 1983, Sandia National Laboratories, Albuquerque, NM.

⁸T. G. Shawki, R. J. Clifton, and G. Majda, "Analysis of Shear Strain Localization in Thermal Visco-Plastic Materials," Brown University Report ARO DAAG29-81-K-0121/3, October 1983, Providence, RI.

first, and then after a fairly long run-in time, it accelerates rapidly, goes over an abrupt peak, and finally begins a slow decline. The temperature begins with a slow but steady increase and then rises very rapidly at the end, whereas the stress begins with a slow decrease and then drops rapidly at the end. It is during the period of most rapid change that the shear band takes recognizable shape.

Figure 6 shows the same three functions as in Figure 5, but at a point near the boundary. Here the plastic strain rate decreases slowly at first, and after the run-in time, it drops sharply and finally makes a rapid but smooth transition to zero. Since plastic work ceases towards the end, the temperature arrives at a plateau, but the stress continues to drop on into the elastic region. Comparison of the stress curves shows that, although central and edge stresses are nearly equal during the run-in time, the edge stress actually drops later than the central stress. Thus the curves indicate that the stress in the center drops rapidly because of thermal softening, but the stress at the edge drops because of momentum transfer. Since the average strain rate is constant, the stress/time plot may be interpreted as a stress/average strain plot. This is shown in Figure 3.

REFERENCES

- 1. R. J. Clifton, J. Duffy, K. A. Hartley, and T. G. Shawki, "On Critical Conditions for Shear Band Formation at High Strain Rates," Scripta Metallurgica 18, p.443-448 (1984).
- 2. A. E. Green and P. M. Naghdi, "A General Theory of an Elastic-Plastic Continuum," Arch. Rat. Mech. Anal. 18, p. 252-281 (1965).
- 3. M. B. Rubin, "A Thermoelastic-Viscoplastic Model with a Rate-Dependent Yield Strength," J. Appl. Mech. 49, p. 305-311 (1982).
- 4. W. H. Drysdale, "The Theory of Plasticity with Rate Effects," ARBRL-TR-02559, ADA 142 102, May 1984, Ballistic Research Laboratory, Aberdeen Proving Ground, MD.
- 5. T. W. Wright and R. C. Batra, "Adiabatic Shear in Simple and Dipolar Materials," to appear (1985).
- 6. A. E. Green, B. C. McInnis, and P. M. Naghdi, "Elastic-Plastic Continua with Simple Force Dipole," Int. J. Eng. Sci. 6, p. 373-394 (1968).
- 7. T. J. Burns, "Approximate Linear Stability Analysis of a Model of Adiabatic Shear Band Formation," Sandia Report SAND83-1907, October 1983, Sandia National Laboratories, Albuquerque, NM.
- 8. T. G. Shawki, R. J. Clifton, and G. Majda, "Analysis of Shear Strain Localization in Thermal Visco-Plastic Materials," Brown University Report ARO DAAG29-81-K-0121/3, October 1983, Providence, RI.




Figure 1. Shearing of a finite block of material with displacement u and temperature change θ .




Figure 2. Yield surface in stress-temperature space.




Figure 3. Stress-strain response curves for a block of material in shear.




Figure 4. Temperature distribution in a finite block of material at various times as a shear band forms.




Figure 5. Stress, temperature, and plastic strain rate vs. time near the center of a block of material as a shear band forms.




Figure 6. Stress, temperature, and plastic strain rate vs. time near the edge of a block of material as a shear band forms.

No. of Copies

Organization

No. of Copies

Organization

- 12 Administrator
 Defense Technical Info Center
 ATTN: DTIC-DDA
 Cameron Station
 Alexandria, VA 22304-6145
- 1 Director
 Defense Advanced Research
 Projects Agency
 ATTN: Tech Info
 Dr. E. Van Reuth
 1400 Wilson Boulevard
 Arlington, VA 22209
- 1 Deputy Assistant Secretary of the Army (R&D) Department of the Army Washington, DC 20310
- 1 HQDA DAMA-ART-M Washington, DC 20310
- 1 Commandant
 Command and General Staff
 College
 ATTN: Archives
 Fort Leavenworth, KS 66027
- 1 Commander
 US Army War College
 ATTN: Lib
 Carlisle Barracks, PA 17013
- 1 Commander
 US Army Materiel Command
 ATTN: AMCDRA-ST
 5001 Eisenhower Avenue
 Alexandria, VA 22333-0001

7 Commander
Armament R&D Center
US Army AMCCOM
ATTN: SMCAR-TSS
SMCAR-TDC
SMCAR-LC, J. Frasier
SMCAR-LCA, T. Davidson
SMCAR-SC, J. D. Corrie

J. Beetle E. Bloore

Dover, NJ 07801

- 1 Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299
- Director
 Benet Weapons Laboratory
 Armament R&D Center
 US Army AMCCOM
 ATTN: SMCAR-LCB-TL
 Watervliet, NY 12189
- 6 Commander
 Benet Weapons Laboratory
 ATTN: Dr. M. A. Hussain
 Dr. Julian Wu
 Dr. John Underwood
 Mr. D. P. Kindall
 Dr. J. Throup
 Dr. E. Schneider
 Watervliet, NY 12189
- 1 Commander
 US Army Aviation Research and
 Development Command
 ATTN: AMSAV-E
 4300 Goodfellow Boulevard
 St. Louis, MO 63120

No. of Copies	Organization	No. of Copies	Organization
---------------	--------------	---------------	--------------

- 1 Commander
 US Army Communications Electronics Command
 Command
 ATTN: AMSEL-ED
 Fort Monmouth, NJ 07703
- 1 Commander
 US Army Electronics Research
 and Development command
 Technical Support Activity
 ATTN: DELSD-L
 Fort Monmouth, NJ 07703-5301
- 1 Commander US Army Harry Diamond Laboratory ATTN: DELHD-TA-L 2800 Powder Mill Road Adelphi, MD 20783
- 1 Commander
 US Army Development and
 Employment Agency
 ATTN: MODE-TED-SAB
 Fort Lewis, WA 98433
- 1 Commander
 US Army Missile Command
 ATTN: AMSMI-R
 Redstone Arsenal, AL 35898
- 1 Commander
 US Army Missile Command
 ATTN: AMSMI-YDL
 Redstone Arsenal, AL 35898
- 1 Commander
 US Army Belvoir R&D Center
 ATTN: STRBE-WC
 Tech Library (Vault), B1dg 315
 Ft. Belvoir, VA 22060-5606

- 1 Commander US Army Natick Research and Development Center ATTN: DRDNA-DT, Dr. D. Sieling Natick, MA 01762
- 1 Commander US Army Tank Automotive Command ATTN: AMSTA-TSL Warren, MI 48090
- 1 Director
 US Army TRADOC Systems
 Analysis Activity
 ATTN: ATAA-SL
 White Sands Missile Range,
 NM 88002
- 1 Commander
 US Army Electronics Proving
 Ground
 ATTN: Tech Lib
 Fort Huachuca, AZ 85613
- 1 Commandant
 US Army Infantry School
 ATTN: ATSH-CD-CSO-OR
 Fort Benning, GA 31905
- 1 Director
 US Army Advanced BMD
 Technology Center
 ATTN: CRDABH-5, W. Loomis
 P. O. Box 1500, West Station
 Huntsville, AL 35807
- 3 Commander
 US Army Materiel and Mechanics
 Research Center
 ATTN: AMXMR-T, J. Mescall
 AMXMR-T, R. Shea
 AMXMR-H, S. C. Chou
 Watertown, MA 02172

No. of		No. of	
Copies	<u>Organization</u>	Copies	Organization
5	Commander US Army Research Office Durham ATTN: Dr. R. Weigle Dr. E. Saibel Dr. G. Mayer Dr. F. Smeideshoff		AFELM, The Rand Corporation ATTN: Library-D 1700 Main Street Santa Monica, CA 90406
	Dr. J. Chandra P. O. Box 12211 Research Triangle Park, NC 27709-2211		Commander US Naval Research Laboratory ATTN: C. Sanday R. J. Weimer Code 5270, F. MacDonald
2	Commander US Army Standarization Group (Europe) ATTN: Dr. B. Steverding		Code 2020, Tech Lib Code 7786, J. Baker Washington, DC 20375
	Dr. F. Rothwarf Box 65 FPO NY 09510		Commander US Naval Research Laboratory Engineering Materials Division ATTN: E. A. Lange
			G. R. Yoder
1	Office of Naval Research Department of the Navy ATTN: Code 402 Washington, DC 20360		C. A. Griffis R. J. Goode R. W. Judy, Jr. A. M. Sullivan R. W. Crooker
1	US Naval Air Systems Command ATTN: AIR-604	5	Washington, DC 20375 Air Force Armament Laboratory
	Washington, DC 20360		ATTN: AFATL/DLODL J. Foster
1	AUL (3T-AUL-60-118) Maxwell AFB, AL 36112		John Collins Joe Smith Guy Spitale Eglin AFB, FL 32542-5000
3	Commander Naval Surface Weapons Center ATTN: Dr. W. H. Holt Dr. W. Mock Tech Lib Dahlgren, VA 22448	1	RADC (EMTLD, Lib) Griffiss AFB, NY 13441
3	Commander Naval Surface Weapons Center ATTN: Dr. R. Crowe Code R32, Dr. S. Fishman Tech lib Silver Spring, MD 20910		
	. 0, 12		

No. of No. of Copies Organization Copies Organization 2 Air Force Wright Aeronautical 1 Honeywell, Inc. Laboratories Defense Systems Division Air Force Systems Command ATTN: Dr. Gordon Johnson Materials Laboratory 600 Second Street, NE ATTN: Dr. Theodore Nicholas Hopkins, MN 55343 Dr. John P. Henderson Wright-Patterson AFB, 1 AFWL/SUL OH 45433 Kirtland AFB, NM 87117 1 Director Environmental Science Service 2 Orlando Technology, Inc. ATTN: Dr. Daniel Matuska Administration US Department of Commerce Dr. John J. Osborn Boulder, CO 80302 P. O. Box 855 Shalimar, FL 32579 1 Director Lawrence Livermore Laboratory 7 SRI International ATTN: Dr. M. L. Wilkins ATTN: Dr. George Abrahamson P. O. Box 808 Dr. Donald R. Curran Livermore, CA 94550 Dr. Donald A. Shockey Dr. Lynn Seaman 6 Sandia Laboratories Mr. D. Erlich ATTN: Dr. L. Davison Dr. A. Florence Dr. P. Chen Dr. R. Caligiuri Dr. L. Bertholf 333 Ravenswood Avenue Dr. W. Herrmann Menlo Park, CA 94025 Dr. J. Nunziato Dr. S. Passman 1 System Planning Corporation Albuquerque, NM 87115 ATTN: Mr. T. Hafer 1500 Wilson Boulevard 1 Director Arlington, VA 22209 US Army Air Mobility Research and Development Laboratory 1 Terra-Tek, Inc. Ames Research Center ATTN: Dr. Arfon Jones Moffett Field, CA 94035 420 Wakara Way University Research Park Salt Lake City, UT 84108 1 Director Jet Propulsion Laboratory 6 Brown University ATTN: Lib (TDS) Division of Engineering 4800 Oak Grove Drive ATTN: Prof. R. Clifton Pasadena, CA 91109 Prof. H. Kolsky Prof. L. B. Freund 1 Aeronautical Research Prof. A. Needleman Associates of Princeton. Prof. R. Asaro Incorporated Prof. R. James

Providence, RI 02912

ATTN: Ray Gogolewski

McLean, VA 22102

1800 Old Meadow Rd., #114

No. of Copies		No. of Copies	
3	California Institute of Technology Division of Engineering and Applied Science ATTN: Dr. J. Mikowitz Dr. E. Sternberg		Harvard University Division of Engineering and Applied Physics ATTN: Prof. J. R. Rice Cambridge, MA 02138
3	Dr. J. Knowles Pasadena, CA 91102 Carnegie-Mellon University	2	Iowa State University Engineering Research Laboratory ATTN: Dr. G. Nariboli
,	Department of Mathematics ATTN: Dr. D. Owen Dr. M. E. Gurtin		Dr. A. Sedov Ames, IA 50010
2	Dr. B. D. Coleman Pittsburgh, PA 15213 Catholic University of America School of Engineering and Architecture	2	Center for the Application of Mathematics ATTN: Dr. E. Varley Dr. R. Rivlin
	Architecture ATTN: Prof. A. Durelli Prof. J. McCoy Washington, DC 20017	1	Bethlehem, PA 18015 New York University Department of Mathematics
6	Cornell University Department of Theoretical and Applied Mechanics		ATTN: Dr. J. Keller University Heights New York, NY 10053
	ATTN: Dr. Y. H. Pao Dr. G. S. S. Ludford Dr. A. Ruoff Dr. J. Jenkins Dr. R. Lance Dr. F. Moon Ithaca, NY 14853	1	North Carolina State University Department of Civil Engineering ATTN: Prof. Y. Horie Raleigh, NC 27607
1	University of Denver Denver Research Institute ATTN: Dr. R. Recht P. O. Box 10127	1	Pennsylvania State University Engineering Mechanical Dept. ATTN: Prof. N. Davids University Park, PA 16802
2	Denver, CO 80210 Forrestal Research Center	3	Rensselaer Polytechnic Institute
2	Aeronautical Engineering Lab. Princeton University ATTN: Dr. S. Lam Dr. A. Eringen Princeton, NY 08540		ATTN: Prof. E. H. Lee Prof. E. Krempl Prof. J. Flaherty Troy, NY 12181

No. of		No. of	
2	Rice University ATTN: Dr. R. Bowen Dr. C. C. Wang P. O. Box 1892 Houston, TX 77001	3	University of California ATTN: Dr. M. Carroll Dr. W. Goldsmith Dr. P. Naghdi Berkeley, CA 94720
1	Southern Methodist University Solid Mechanics Division ATTN: Prof. H. Watson Dallas, TX 75222	1	University of California Dept of Aerospace and Mechanical Engineering Science ATTN: Dr. Y. C. Fung
1	ATTN: Dr. Charles Anderson 6220 Culebra Road		P. O. Box 109 La Jolla, CA 92037
	P. O. Box Drawer 28510 San Antonio, TX 78228	1	University of California Department of Mechanics ATTN: Dr. R. Stern
2	Southwest Research Institute Department of Mechanical Sciences		504 Hilgard Avenue Los Angeles, CA 90024
	ATTN: Dr. U. Kindholm Dr. W. Baker 8500 Culebra Road San Antonio, TX 78228	1	University of California at Santa Barbara Dept of Mechanical Engineering ATTN: Prof. T. P. Mitchel Santa Barbara, CA 93106
1	Temple University College of Engineering	1	University of Dayton Research
	Technology ATTN: Dr. R. Haythornthwaite Dean Philadelphia, PA 19122		Institute ATTN: Dr. S. J. Bless Dayton, OH 45469
	,	1	University of Delaware
4	The Johns Hopkins University ATTN: Prof. R. B. Pond, Sr. Prof. R. Green Prof. W. Sharpe		Dept of Mechanical Engineering ATTN: Prof. J. Vinson Newark, DE 19711
	Prof. J. Bell 34th and Charles Streets Baltimore, MD 21218	1	University of Delaware Dept of Mechanical and Aerospace Engineering
1	Tulane University Dept of Mechanical Engineering ATTN: Dr. S. Cowin New Orleans, LA 70112		ATTN: Dr. Minoru Taya Newark, DE 19711

No. of Copies		No. of Copies	
3	University of Florida Dept. of Engineering Science and Mechanics ATTN: Dr. C. A. Sciammarilla Dr. L. Malvern Dr. E. Walsh Gainesville, FL 32611		University of Minnesota Dept. of Aerospace Engineering and Mechanics ATTN: Prof. J. L. Erickson 107 Akerman Hall Minneapolis, MN 55455
2	University of Houston Department of Mechanical Engineering ATTN: Dr. T. Wheeler Dr. R. Nachlinger Houston, TX 77004		University of Pennsylvania Towne School of Civil and Mechanical Engineering ATTN: Prof. Z. Hashin Philadelphia, PA 19104 University of Texas
1			Department of Engineering Mechanics ATTN: Dr. M. Stern Dr. M. Bedford Prof. Ripperger
1	University of Illinois Dept. of Theoretical and Applied Mechanics ATTN: Dr. D. Carlson	1	Dr. J. T. Oden Austin, TX 78712 University of Washington
1	University of Illinois at Chicago Circle College of Engineering	'	Dept. of Aeronautics and Astronautics ATTN: Dr. Ian M. Fyfe 206 Guggenheim Hall Seattle, WA 98105
2	Dept. of Materials Engineering ATTN: Dr. T. C. T. Ting P. O. Box 4348 Chicago, IL 60680 University of Kentucky	2	Washington State University Department of Physics ATTN: Dr. R. Fowles Dr. G. Duvall Pullman, WA 99163
6 _	Dept. of Engineering Mechanics ATTN: Dr. M. Beatty Prof. O. Dillon, Jr. Lexington, KY 40506	2	
1	University of Florida ATTN: Graduate Research Professof Engr Sciences (Dr. Daniel C. Drucker) 231 Aerospace Engineering Bldg Gainesville, FL 32611	1	New Haven, CT 06520 University of Missouri- Rolla Department of Engineering Mechanics ATTN: Romesh C. Batra Rolla, MO 65401-0249

No. of Copies

Organization

No. of Copies

Organization

Aberdeen Proving Ground

Dir, USAMSAA

ATTN: AMXSY-D

AMXSY-MP, H. Cohen

Cdr, USATECOM

ATTN: AMSTE-TO-F

Cdr, CRDC, AMCCOM

ATTN: SMCCR-RSP-A

SMCCR-MU

SMCCR-SPS-IL

USER EVALUATION SHEET/CHANGE OF ADDRESS

reports it	atory undertakes a continuing effort to improve the quality of the publishes. Your comments/answers to the items/questions below will our efforts.
1. BRL Rej	port NumberDate of Report
2. Date Re	eport Received
3. Does the other area	of interest for which the report will be used.)
4. How spedata, proce	ecifically, is the report being used? (Information source, design edure, source of ideas, etc.)
as man-hour	e information in this report led to any quantitative savings as far es or dollars saved, operating costs avoided or efficiencies achieved o, please elaborate.
	Comments. What do you think should be changed to improve future (Indicate changes to organization, technical content, format, etc.)
	Name
CURRENT	Organization
ADDRESS	Address
	City, State, Zip
7. If indio	cating a Change of Address or Address Correction, please provide the ect Address in Block 6 above and the Old or Incorrect address below.
	Name
OLD ADDRESS	Organization
ADDALOG	Address
	City, State, Zip

(Remove this sheet along the perforation, fold as indicated, staple or tape closed, and mail.)